

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/081,238	02/25/2002	Masanobu Hidehira	8039-1002	3861
466 75	590 10/04/2005		EXAMINER	
YOUNG & THOMPSON		DI GRAZIO, JEANNE A		
745 SOUTH 23RD STREET 2ND FLOOR			ART UNIT	PAPER NUMBER
ARLINGTON,	VA 22202		2871	

DATE MAILED: 10/04/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

•			SK
	Application No.	Applicant(s)	
·	10/081,238	HIDEHIRA ET AL	.
Office Action Summary	Examiner	Art Unit	
	Jeanne A. Di Grazio	2871	
The MAILING DATE of this communication ap Period for Reply	ppears on the cover sheet	with the correspondence ac	ddress
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING I - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statu Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMU .136(a). In no event, however, may d will apply and will expire SIX (6) No te, cause the application to become	NICATION. The a reply be timely filed SONTHS from the mailing date of this of ABANDONED (35 U.S.C. § 133).	
Status			
 1) ⊠ Responsive to communication(s) filed on 15. 2a) ☐ This action is FINAL. 2b) ⊠ Th 3) ☐ Since this application is in condition for allows closed in accordance with the practice under 	is action is non-final. ance except for formal m	• •	e merits is
Disposition of Claims			
4) □ Claim(s) 1,4-9 and 12-15 is/are pending in the 4a) Of the above claim(s) is/are withdra 5) □ Claim(s) is/are allowed. 6) □ Claim(s) 1,4-9 and 12-15 is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/	awn from consideration.		
Application Papers			
9) The specification is objected to by the Examin 10) The drawing(s) filed on is/are: a) ac Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examin	cepted or b) objected e drawing(s) be held in abey ction is required if the drawi	vance. See 37 CFR 1.85(a). ng(s) is objected to. See 37 C	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreig a) All b) Some * c) None of: 1. Certified copies of the priority documer 2. Certified copies of the priority documer 3. Copies of the certified copies of the pri application from the International Burea * See the attached detailed Office action for a list	nts have been received. nts have been received ir ority documents have be au (PCT Rule 17.2(a)).	n Application No en received in this National	Stage
Attachment(s) Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08 Paper No(s)/Mail Date	Paper N	w Summary (PTO-413) Io(s)/Mail Date of Informal Patent Application (PTO	0-152)

Application/Control Number: 10/081,238

Art Unit: 2871

DETAILED ACTION

Claims

Claims 1, 4-9, and 12-15 are pending. Claims 2 and 10 have previously been cancelled.

Claims 11-15 have previously been added. Claims 3 and 11 have been cancelled per previous

Amendment.

Priority

Priority to Japanese Patent Application No. 2001-049492 (Feb. 23, 2001) is claimed.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1, 4, 5, 9 and 12 are rejected under 35 U.S.C. 103(a) as being unpatentable over United States Patent 6,147,722 (to Shimada et al.) in view of Japanese Patent Application No. 2000-231123 (Aug. 22, 2000)(to Nakata et al.).

Application/Control Number: 10/081,238

Art Unit: 2871

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

As to claim 1 (amended), Shimada discloses a pair of substrates (Prior Art Figure 28, substrates 120 and 122), a liquid crystal sealed between said pair of substrates (Figure 28 LC 112), a plurality of gate signal lines and source signal lines crossing each other (Figures 16 A&B and 19), a switching element having one end of a current path connected to the corresponding data line and a control end connected to the corresponding scanning line (Figures 16 A&B and 19), a wiring connected to the other end of the current path of the switching element (Figures 16 A&B and Figure 19), an insulating layer being formed on said wiring and having a contact hole through which an end portion of said wiring is exposed (insulating film 136 of Figure 28), a pixel electrode being formed on said insulating layer and electrically connected to the end portion of said wiring through the contact hole (Figure 19, pixel 140); and an alignment film being formed on said pixel electrode and in contact with said liquid crystal (Figure 28, alignment film 150), wherein said contact hole is formed at a position overlapping a region where disclination occurs (Figure 16A and Figure 16B).

Please note that the pixel electrode is connected to the switching element through at least a wiring. The wirings of the switching element all have at least some type of shielding property.

Shimada does not appear to explicitly specify wherein said insulating layer is formed of a plurality of laminated insulating films, the insulating films have openings individually which form said contact hole in a tapered shape as a whole <u>and wherein said insulating films includes a passivation film formed on the switching element, a color layer formed on said passivation film, and a flattening film formed on said passivation film and color layer, said contact hole includes openings formed in the passivation film, the color layer, and the flattening film, respectively, and the openings being formed in a tapered shape as a whole.</u>

Nakata teaches and discloses a liquid crystal display with filter and light shield separated from contact hole and shows in Figures 3, 5, 7 and 8, a passivation layer (8), a color filter (13) and an overcoat layer (14) in which a contact hole (11) is formed in all three layers into a tapered shape as can be seen in the figures.

It would have been obvious to one of ordinary skill in the art of liquid crystals at the time the invention was made to modify Shimada in view of Nakata for efficient backlight, etching that can be executed easily and reliably, decreased contact resistance of a contact hole and elimination of light leakage (entire patent application).

As to claim 4, the wiring is made of a light shielding material and said contact hole and at least a part of the region where disclination occurs are shielded by said wiring (Shimada Column 7, Lines 61-63).

As to claim 5, the scanning lines and the data lines bounds a plurality of pixels each having said contact hole and said contact hole in the pixel is provided at a downstream in a rubbing direction with respect to the switching element of other pixel adjacent to the pixel (Shimada Column 14, Lines 45-57).

Art Unit: 2871

As to claim 9 (amended), Applicant's recited method steps would have been obvious to one of ordinary skill in the art of liquid crystals at the time the invention was made in view of the devices as taught and disclosed by Shimada and Nakata.

As to claim 12, the boundary of the first and second regions of on source signal lines is covered with a light-shading film (Column 7, Lines 49-52).

Claims 6-8 are rejected under 35 U.S.C. 103(a) as being unpatentable over United States Patent 6,147,722 (to Shimada et al.) in view of Japanese Patent Application No. 2000-231123 (Aug. 22, 2000)(to Nakata et al.) and further in view of United States Patent 5,831,707 (to Ota et al.).

As to claims 6 and 7 (both amended), Shimada does not appear to explicitly specify that the scanning line has a projecting portion overlapping at least one of the contact hole and region where disclination occurs the projection portion of the scanning line shielding light, a black matrix has a first portion that is wider than other portions of said black matrix and that overlaps a region in the pixel between said data line and the projecting portion and the projecting portion forms an electrostatic capacitance between the wiring.

Ota teaches and discloses an active matrix type liquid crystal display apparatus in which an insulating black matrix is formed at an interval between a pixel electrode and projection portion of a scan line (Column 22, Lines 29-33). The interval between the pixel electrode and projection portion is a necessary interval (Id.). The unnecessary intervals to which the reference refers, are those intervals other than the necessary interval between the pixel electrode and the scan line. Such a configuration improves contrast ratio (Id.).

Art Unit: 2871

Therefore it would have been obvious to one of ordinary skill in the art of liquid crystals at the time the invention was made to modify Shimada in view of Ota for improved contrast ratio.

As to claim 8 (amended), the projection portion of the scan line forms an electrostatic capacitance.

Claim 13 is rejected under 35 U.S.C. 103(a) as being unpatentable over United States Patent 6,147,722 (to Shimada et al.) in view of United States Patent 5,831,707 (to Ota et al.).

As to claim 13 (amended), Shimada discloses a pair of substrates (Prior Art Figure 28, substrates 120 and 122), a liquid crystal sealed between said pair of substrates (Figure 28 LC 112), a plurality of gate signal lines and source signal lines crossing each other (Figures 16 A&B and 19), a switching element having one end of a current path connected to the corresponding data line and a control end connected to the corresponding scanning line (Figures 16 A&B and 19), a wiring connected to the other end of the current path of the switching element (Figures 16 A&B and Figure 19), an insulating layer being formed on said wiring and having a contact hole through which an end portion of said wiring is exposed (insulating film 136 of Figure 28), a pixel electrode being formed on said insulating layer and electrically connected to the end portion of said wiring through the contact hole (Figure 19, pixel 140); and an alignment film being formed on said pixel electrode and in contact with said liquid crystal (Figure 28, alignment film 150), wherein said contact hole is formed at a position overlapping a region where disclination occurs (Figure 16A and Figure 16B). The wiring is made of a light shielding material and said contact

Application/Control Number: 10/081,238

Art Unit: 2871

hole and at least a part of the region where disclination occurs are shielded by said wiring (Shimada Column 7, Lines 61-63).

Please note that the pixel electrode is connected to the switching element through at least a wiring. The wirings of the switching element all have at least some type of shielding property.

Shimada does not appear to explicitly specify a black matrix overlapping data lines and that has a wide portion overlapping a region in the pixel between said data line and the projecting portion.

Ota teaches and discloses an active matrix type liquid crystal display apparatus in which an insulating black matrix is formed at an interval between a pixel electrode and projection portion of a scan line (Column 22, Lines 29-33). The interval between the pixel electrode and projection portion is a necessary interval (Id.). The unnecessary intervals to which the reference refers, are those intervals other than the necessary interval between the pixel electrode and the scan line. Such a configuration improves contrast ratio (Id.).

Therefore it would have been obvious to one of ordinary skill in the art of liquid crystals at the time the invention was made to modify Shimada in view of Ota for improved contrast ratio.

Claims 14 and 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over United States Patent 6,147,722 (to Shimada et al.) in view of United States Patent 5,831,707 (to Ota et al.) and further in view of Japanese Patent Application No. 2000-231123 (Aug. 22, 2000)(to Nakata et al.).

As to claims 14 and 15, Shimada does not appear to explicitly specify wherein said insulating layer is formed of a plurality of laminated insulating films, the insulating films have

Application/Control Number: 10/081,238 Page 8

Art Unit: 2871

openings individually which form said contact hole in a tapered shape as a whole or that the insulating films include a passivation film formed on the switching element, a color layer formed on the passivation film and a flattening film formed on the passivation film and color layer where the contact hole includes openings formed in the passivation film, the color layer, and the flattening film respectively and the openings being formed in a tapered shape as a whole.

Nakata teaches and discloses a liquid crystal display with filter and light shield separated from contact hole and shows in Figures 3, 5, 7 and 8, a passivation layer (8), a color filter (13) and an overcoat layer (14) in which a contact hole (11) is formed in all three layers into a tapered shape as can be seen in the figures.

It would have been obvious to one of ordinary skill in the art of liquid crystals at the time the invention was made to modify Shimada in view of Nakata for efficient backlight, etching that can be executed easily and reliably, decreased contact resistance of a contact hole and elimination of light leakage (entire patent application).

Application/Control Number: 10/081,238 Page 9

Art Unit: 2871

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Jeanne A. Di Grazio whose telephone number is (571)272-2289.

The examiner can normally be reached on M-F.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Robert Kim, can be reached on (571)272-2293. The fax phone number for the

organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Jeanne Andrea Di Grazio

Patent Examiner

Art Unit 2871

JDG

ANDREW SCHECHTER
PRIMARY EXAMINER